

Bennett CNG

REVOLUTIONARY FUEL WITH THE FAMILIAR FUELING EXPERIENCE

The industry's best frame-to-finish purpose built CNG Dispenser delivers the most features and options available anywhere in the world

Bennett
simply better

INDUSTRIAL GRADE ELECTRONICS

The fueling industry's most powerful and efficient X19 electronics deliver the highest reliability, fastest processing power, and draw only 2 AMPS under load

ATMOSPHERIC AMBIENT TEMPERATURE SENSOR

Measures the outside temperature and automatically adjusts the target fill pressure
***Patented Feature**

NFC

NFC Reader for contactless payment, mobile payment, loyalty and other near-field devices

EMV SECURE PAYMENT

PCI compliant/EMV ready integrated pay-at-the-pump hardware compatible with nearly all POS systems and payment networks

REAL TIME FILL GAUGE

Provides real-time simulation of the customers tank filling during the fueling process
***Patented Feature**

HIGH RESOLUTION DISPLAYS

Available with 7" widescreen or 10.5" color displays with customizable step-by-step user instructions, unrestricted promotional applications and user friendly soft keys

NOZZLE BOOT

All Bennett dispensers use metal nozzle boots to ensure greater durability and long life. They also include a brand specific nozzle holder to secure hanging hardware.

3600

CNG

**Bennett patents secured or pending*

BENNETT CNG SPECIFICATIONS

WITH X19 ELECTRONICS

STANDARD FEATURES

Dimensions: 44.75" w (base) x 94.5" h x 20.5" d (base)

Products: Up to 2 Products

Hoses: Up to 2 Dispensing Hoses

Unit Type: Straight Grade Only

Hydraulics: Remote Only

Displays: LCD 6-Digit 1.4" for Sales
LCD 6-Digit 1.1" for Volume
LCD 4-Digit 1/2" Price Per Volume

Voltage: 115/120/230/240 VAC 50/60 Hz, 560w

Flow Rate: 100 kg/min

Protocol: Bennett Open Protocol

Hydraulics: 3/4" Stainless Steel Hydraulics

Controls and Voltage: Micro-Motion Coriolis Meter, 24VDC 11 Watt Solenoid Valves, 3/4" Vent Line, Ambient Temperature Range of -40°C to +80°C

Regulatory: NTEP Certificate of Conformance, PCI Compliance, NFPA 52, NFPA 496, CSA 12.5-M99, ANSI/IAS NGVA 4.1-1999, MetLab Type Certification for use with purged or non-purged electronics cabinets

Warranty: 12 Months Parts, Labor and Travel

OPTIONAL FEATURES

Payment Options: A variety of payment options are available for the CNG dispenser depending on your needs.

- EMV: 7" Widescreen or 10.5" Display with soft keys, Hybrid Chip EMV Card Reader, PCI Compliant EMV ready EPP, High Speed Receipt Printer
- Full-EMV: Full EMV payment with 7" or 10.5" Display (require dispenser hub board and in-store hub box)
- CREDIT-ALPHA: **Alphanumeric** integrated pay-at-the-pump system with 7" display for fleet and long-haul consumers
- NFC reader for contact-less payment, mobile payment, loyalty and other near-field devices
- Customer Branded Graphics provide valuable brand recognition and loyalty

Other Options: Single or Dual Sided, 3000 or 3600 PSI Service Pressure, Single, Dual or Three Bank Inlets, Internal Methane Detector for Non-Purge Cabinets, X-Purge Blower Kit, Pressure Regulator, Exterior Mounted Methane Detector, Ball Valves

DIMENSIONS

